

12. SPECIFICATIONS

Model UMK425U

Frame

| Type | LGU | UGU |
|--|--|-----------|
| Handle type | Loop | U-shaped |
| Overall length (with 4-tooth blade) | 1860 (1880) | |
| Overall width | 320 (350) | 610 |
| Overall height | 250 | 430 (400) |
| Dry weight (without cutting head) | 5.7 | 5.9 |
| Clutch type | Centrifugal clutch | |
| Cutter | Nylon-line: Tap & Go Type(420mm) Cutting blade: 4-teeth blade (230mm) | |

Applicable debris shield

| Type | LGU | UGU |
|--------------------------------|-----|-----|
| For nylon-line cutting head | ○ | ○ |
| For cutting blade | ○ | ○ |

NOTE:

Specifications may vary according to the types, and are subject to change without notice.

Engine

| | |
|--------------------|-------------------------------------|
| MODEL | UMK425U |
| Engine model | GX25 |
| Engine type | 4-stroke,overhead valve, 1 cylinder |
| Displacement | 25cm ³ |
| Bore X Stroke | 35mm X26mm |
| Max. output | 0.81Kw(1.1ps)/7,000rpm |
| Max. torque | 1.25N · m(0.13kg · m)/5,000rpm |
| Fuel consumption | 340g/kWh(250g/PSh) |
| Cooling system | Forced air |
| Ignition system | Transistor Magneto |
| Oil capacity | 0.08l |
| Fuel tank capacity | 0.55l |
| Spark plug | NGK:CMR5H |

NOTE:

Specifications may vary according to the types, and are subject to change without notice.

Model UMK435U

Frame

| Type | LHU/LGU | UHU/UGU |
|--|--|-----------|
| Handle type | Loop | U-shaped |
| Overall length (with 4-tooth blade) | 1865 (1900) | |
| Overall width | 320 (350) | 610 |
| Overall height | 260 | 455 (425) |
| Dry weight (without cutting head) | 6.9 | 7.2 |
| Clutch type | Centrifugal clutch | |
| Cutter | Nylon-line: Manual type (444mm) (LHU/UHU) Tap & Go Type (444mm) (LGU/UGU) Cutting blade: 4-teeth blade (255mm) | |

Applicable debris shield

| Type | LHU/LGU | UHU/UGU |
|--------------------------------|---------|---------|
| For nylon-line cutting head | ○ | ○ |
| For cutting blade | ○ | ○ |

NOTE:

Specifications may vary according to the types, and are subject to change without notice.