

HELI**FORKLIFT TRUCK****STANDARD DISTRIBUTION**

Wide view mast
Class-III carriage
Loading bracket
Standard fork
Deluxe rubber floor mat
Dipstick for tor-con oil
J-lug long lift tire
Overhead guard canvas
Dipstick for hydraulic oil
Overhead guard
Overhead air intake
Return hydraulic filter
Standard seat
Steering indicator
Transmission fuel filter
Cyclone air cleaner
Lamp bracket
Flow regulator on lift oil way
Toggle type parking break lever
Full hydraulic power steering
Overhead lamp
Lifting & tilting control lever
Hour metre

OPTIONS AND MISCELLANEOUS

Dual drive wheel with fender
Solid pneumatic tire
Decreases black smoke fire proof silencer
Enclosed cab
Catalytic muffler
Heater
Overhead exhaust system
Dual air cleaner
Fire extinguisher
Suspension seat
Boot for tilt cylinder and steering cylinder
Dual fuel system (lpg/gasoline)
Rear working light
Custom color paint
Steel mesh for protection
Turning warning light
Enterable container overhead guard

OPTIONAL ATTACHMENT

Enterable container wide view double mask with full free length
Enterable container wide view triple mask with full free length
Wide view full free 2-stage heighten mast
Wide view double mask with full free length
Wide view triplex mask with full free length
Side shifter
Widened fork holder
Damp fork
Lengthened fork
Damp container
Turning flat clip
Sleeve on fork
Load hawk
Paper clip
Multi function barrel clip
Boom

Tools

Ignition key engine stop
Fuse broken circuit indication

Specification of Optional High Power Engine

Internal Combustion Engine Model	R4105	TB42A4GR1	S6S-31TEL	GM4.3L	S6S-Y3T31TEL
Model	weichai	NISSAN	mitsubishi	GM	mitsubishi
Kw(ps)/r.p.m	59/2300	66/2300	64.7/2300	61/2300	64/2300
Rate torque Nm/rpm	280/1600-1800	310/1800	284/1600	280/1400	293/1700
Internal Combustion Engine Number of Cylinder	4	6	6	V6	6
Internal Combustion Engine displacement	4.156	4.169	4.996	4.294	4.996
Applicable truck model	CPQD40/45/50WF	CPQD40/45/50R	CPQD40/45/50S&12	CPYD40/45/50-TY1	CPQD40/45/50S&34

STANDARD SPECIFICATION**ANHUI HELI CO., LTD.**

Manufacturer	ANHUI HELI CO., LTD.				
Model	CPQD40	CPCD45	CPYD40 CPQD40 CPQYD40	CPYD45 CPQD45 CPQYD45	CPYD50 CPQD50 CPQYD50
Load Capacity	kg	4000	4500	5000	4500
Load Center	mm	500			
Tire Type	Air-tyre				
Lifting Speeds (With load/Without load)	mm/s	450/455	430/435	450/455	450/455
Lowering Speeds (With load/Without load)	mm/s	≤595	≤595	≤595	≤595
Free lift	mm	150	150	150	150
Max. Driving Speeds (With load/Without load)	km/h	24	24	24	24
Outside turning radius	mm	2720	2800	2720	2740
Max. Gradeability (With load/Without load)	%	19/20	15/17	19/20	16/18
Max. Towing (With load/Without load)	N	21000/17800			
Overall height (overhead guard)	mm	2270 (2230)			
Overall Lowered Height	mm	2375			
Overall Raised Height	mm	4200			
Goods fork (L×W×T)	mm	1070*150*55			
Tire (Front)		300-15-18PR			
Tire (Rear)		7.00-12-12PR			
Min. under-clearance (bottom of mast)	mm	158			
Weight distribution of axle with load(front/rear)	kg	9010/1590	10500/1600	9010/1590	9750/1550
Weight distribution of axle without load(front/rear)	kg	2750/3850	2680/4420	2750/3850	2710/4090
Battery Voltage / Capacity	V/Ah	2-12v/70Ah/20h		1-12v/100Ah/20h	
Service Brake		Brake-foot step type			
Parking Brake		Mechanical-hand brake way			
Internal Combustion Engine Fuel Tank Capacity	L	90			
Transmission Number of Speed Fwd/Rvs-Type		2/1			
Total Weight	kg	6600	7100	6600	7100