

**HELI****FORKLIFT TRUCK****STANDARD DISTRIBUTION**

Wide view mast  
Class-III carriage  
Loading bracket  
Standard fork  
Deluxe rubber floor mat  
Dipstick for tor-con oil  
J-lug long lift tire  
Overhead guard canvas  
Dipstick for hydraulic oil  
Overhead guard  
Overhead air intake  
Return hydraulic filter  
Standard seat  
Steering indicator  
Transmission fuel filter  
Cyclone air cleaner  
Lamp bracket  
Flow regulator on lift oil way  
Toggle type parking break lever  
Full hydraulic power steering  
Overhead lamp  
Lifting & tilting control lever  
Hour metre

**OPTIONS AND MISCELLANEOUS**

Dual drive wheel with fender  
Solid pneumatic tire  
Decreases black smoke fire proof silencer  
Enclosed cab  
Catalytic muffler  
Heater  
Overhead exhaust system  
Dual air cleaner  
Fire extinguisher  
Suspension seat  
Boot for tilt cylinder and steering cylinder  
Dual fuel system (lpg/gasoline)  
Rear working light  
Custom color paint  
Steel mesh for protection  
Turning warning light  
Enterable container overhead guard

**OPTIONAL ATTACHMENT**

Enterable container wide view double mask with full free length  
Enterable container wide view triple mask with full free length  
Wide view full free 2-stage heighten mast  
Wide view double mask with full free length  
Wide view triplex mask with full free length  
Side shifter  
Widened fork holder  
Damp fork  
Lengthened fork  
Damp container  
Turning flat clip  
Sleeve on fork  
Load hawk  
Paper clip  
Multi function barrel clip  
Boom

**Tools**

Ignition key engine stop  
Fuse broken circuit indication

**Specification of Optional High Power Engine**

Internal Combustion Engine Model	R4105	TB42A4GR1	S6S-31TEL	GM4.3L	S6S-Y3T3TFL
Model	weichai	NISSAN	mitsubishi	GM	mitsubishi
Kw(ps)/r.p.m	59/2300	66/2300	64.7/2300	61/2300	64/2300
Rate torque Nm/rpm	280/1600-1800	310/1800	284/1600	280/1400	293/1700
Internal Combustion Engine Number of Cylinder	4	6	6	V6	6
Internal Combustion Engine displacement	4.156	4.169	4.996	4.294	4.996
Applicable truck model	CPCD40/45/50WF	CPQD40/45/50R	CPD40/45/50S3a12	CPYD40/45/50-TY1	CPD40/45/50S3a4

**STANDARD SPECIFICATION****ANHUI HELI CO., LTD.**

Manufacturer	ANHUI HELI CO., LTD.				
Model	CPCD40	CPCD45	CPCD50	CPYD40 CPQD40 CPQYD40	CPYD45 CPQD45 CPQYD45
Load Capacity	kg	4000	4500	5000	4500
Load Center	mm	500			
Tire Type	Air-tyre				
Lifting Speeds (With load/Without load)	mm/s	450/455	430/435	450/455	450/455
Lowering Speeds (With load/Without load)	mm/s	≤595	≤595	≤595	≤595
Free lift	mm	150	150	150	150
Max. Driving Speeds (With load/Without load)	km/h	24	24	24	24
Outside turning radius	mm	2720	2800	2720	2740
Max. Gradeability (With load/Without load)	%	19/20	15/17	19/20	16/18
Max. Towing (With load/Without load)	N	21000/17800			
Overall height (overhead guard)	mm	2270 ( 2230)			
Overall Lowered Height	mm	2375			
Overall Raised Height	mm	4200			
Goods fork (L×W×T)	mm	1070*150*55			
Tire (Front)		300-15-18PR			
Tire (Rear)		7.00-12-12PR			
Min. under-clearance (bottom of mast)	mm	158			
Weight distribution of axle with load(front/rear)	kg	9010/1590	10500/1600	9010/1590	9750/1550
Weight distribution of axle without load(front/rear)	kg	2750/3850	2680/4420	2750/3850	2710/4090
Battery Voltage / Capacity	V/Ah	2-12v/70Ah/20h		1-12v/100Ah/20h	
Service Brake		Brake-foot step type			
Parking Brake		Mechanical-hand brake way			
Internal Combustion Engine Fuel Tank Capacity	L	90			
Transmission Number of Speed Fwd/Rvs-Type		2/1			
Total Weight	kg	6600	7100	6600	6800
		6600	7100	6600	7100