



**FASTENER BREAKDOWN**

■ Applicable nail sizes: mm (in.)

	L	38(1-1/2) – 65(2-1/2)
	d	2.2(.087) – 2.5(.098)
	D	6.7(.264) – 8.3(.327)



**SPECIFICATIONS**

<b>Pressure Range</b>	70 – 120 psi
<b>Capacity</b>	120 nails
<b>Dimensions</b>	406 x 338mm
<b>Weight</b>	3.0kg
<b>Fastener Series</b>	T & F series nails
<b>Standard Accessories</b>	Safety glasses, oiler, hex keys

Note: Specifications may change without Notice

**KEY SELLING POINTS**

- ❖ Bump fire trigger for rapid operation
- ❖ Finish nail driver blade factory fitted ensure minimal blade witness marks when finish nailing
- ❖ Reduced recoil ensures operator safety & comfort
- ❖ Top load magazine for easy reloading of nails
- ❖ 2.2 – 2.5mm fastener diameter extends the range of applications
- ❖ Strong robust design for heavy duty trade applications

**APPLICATIONS**

- ❖ Top nailing hardwood flooring
- ❖ Door jambs
- ❖ Window manufacture
- ❖ Decking & fencing
- ❖ Pallet & crate manufacture
- ❖ Shop fitting & cabinet making