

Historical Specification

To find historical specifications for discontinued equipment, select the product category, model number and first year of production. For additional information, visit the [service and maintenance](#) section or contact your [local dealer](#).

Skid-Steer Loaders

Bobcat S550

n/a

Standard Optional **N/A** Not Applicable

Units Metric

Bobcat S550

Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	45.5 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (SAE)	794 kg
Tipping Load	1588 kg
Operating Weight	2842 kg
Travel Speed	11.9 km/h
Travel Speed (2-speed option)	17.7 km/h

Capacities

Fuel Tank	93.7 l
-----------	--------

Hydraulic System

System Relief @ Quick Couplers	241.32 bar
Auxiliary Std Flow	64.7 l/min
Auxiliary High Flow	101.1 l/min

Dimension

Length	3378 mm
Length without Attachment	2657 mm
Length with Standard Bucket	3378 mm
Width	1643 mm
Width (with bucket)	1727 mm
Height	1976 mm
Height with Operator Cab	1976 mm
Height to Bucket Hinge Pin	2908 mm
Reach @ Maximum Height	432 mm
Turning Radius	2032 mm
Wheelbase	1082 mm

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Adjustable Seat	<input type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Parking Brake	<input type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Rear Window	<input type="checkbox"/>
Top Window	<input type="checkbox"/>
Lift-Arm Support	<input type="checkbox"/>
Seat Belt	<input type="checkbox"/>
Suspension Seat	<input checked="" type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Rear Hydraulics	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.