

Historical Specification

To find historical specifications for discontinued equipment, select the product category, model number and first year of production. For additional information, visit the [service and maintenance](#) section or contact your [local dealer](#).

Compact Track Loaders

Bobcat T140

2008

Standard Optional **N/A** Not Applicable

Units Metric

Bobcat T140

Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	36.5 kW

Performance

Rated Operating Capacity (SAE)	635 kg
Operating Capacity (50% of Tip)	917 kg
Tipping Load	1834 kg
Operating Weight	3021 kg
Travel Speed	11.7 km/h
Ground Pressure (Rubber)	0.36 bar

Capacities

Fuel Tank	58.3 l
-----------	--------

Hydraulic System

System Relief @ Quick Couplers	186.16 bar
Auxiliary Std Flow	64 l/min
Auxiliary High Flow	n/a

Dimension

Length	2433 mm
Length without Attachment	2433 mm
Length with Standard Bucket	3152 mm
Width	1397 mm
Width (with bucket)	1422 mm
Height	1966 mm
Height with Operator Cab	1966 mm
Height to Bucket Hinge Pin	2784 mm
Reach @ Maximum Height	650 mm
Turning Radius	1961 mm
Length of track on ground	1229 mm
Track Width	300 mm

Features

Joystick Control	N/A
Air Conditioning	N/A
Backup Alarm	■
BICS System (Interlock)	■
Cab Heater	☑
Operating Lights	■
Suspension Seat	■
Two Speed Travel	N/A
Deluxe Instrumentation	☑
Engine Shutdown	■
Hydraulic Bucket Positioning	☑
High Flow Option	N/A
Auxiliary Hydraulics	■
Bob-Tach Attachment System	■
Power Bob-Tach	☑
ACS (Switchable Controls)	☑
Ride Control	N/A
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.