

SHARE

Attachments / Spreader Specifications

Units US

	Sand and Salt Spreader	HS8 Spreader
Operating Weight	325 lb	387 lb
Length	78.5 in	32.1 in
Width	48.5 in	54.4 in
Height	44.7 in	40.9 in
Hopper Capacity	13.5 ft ³	9.6 ft ³
Spreading Pattern Min	5 ft	18 ft
Spreading Pattern Max	40 ft	28 ft
Speed Control	Variable Speed Control Dial	Variable, Hydraulic
Motor	12-Volt DC Direct Drive	Hydraulic
Spinner Wheel	12" Diameter	18" diameter

Compatible Carriers

Skid-Steer Loaders		
Bobcat A770		■
Bobcat S450		■
Bobcat S550		■
Bobcat S570		■
Bobcat S590		■
Bobcat S595		■
Bobcat S630		■
Bobcat S650		■
Bobcat S740		■
Bobcat S770		■
Bobcat S850		■
Compact Track Loaders		
Bobcat T450		■
Bobcat T550		■

Bobcat T590			■
Bobcat T595			■
Bobcat T630			■
Bobcat T650			■
Bobcat T740			■
Bobcat T750			■
Bobcat T770			■
Bobcat T870			■

Toolcat™ Work Machine			
Bobcat 5600		■	■
Bobcat 5610			■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.