

Model No — K1620

Plant Name — Spring Mounted Petrol Drive Unit

Manufacture — AG Pulie

Mandatory Personal Protective Equipment —



Foot Protection



Hearing Protection



Protective Clothing



RISK ASSESSMENT INFORMATION

Operator Competency – Plant Licence Not Required

Potential Hazard(s)	Risk Level	Control Measure(s)
Contact with Moving Parts	Low	Do not operate unless all covers and guards are correctly mounted on to the machine.
Contact with hot parts of the engine	Low/Medium	Muffler is fitted with a heat shield. Allow motor to cool down before performing maintenance. Take note of warning labels on the motor.
Explosion or Fire	Medium	Don't refuel while the motor is running or hot. Avoid spilling fuel when refuelling. Follow motor manufacturers instructions for refuel and petrol safety
Hearing damage	Medium/Low	Ensure you are wearing hearing protection rated to the db output of the motor
Manual Handling List	Medium/Low	Always use a two man lift when moving the machine to avoid personal injury.
Poisoning from Fumes	Medium/Low	Always operate the machine in a well-ventilated area. Avoid breathing in petrol fumes.

IMPORTANT

Before using Drive Unit,

Read and understand these operators' instructions

Follow the motor manufacturers instructions for operating the motor

Ensure that the work site is safe and free of hazards

Key Operating Instructions

- 1- Insert the flexible shaft into the housing. It is securely in place when the shaft locking pin returns to original position.
- 2- To start the motor follow the manufacturer's instructions
- 3- When the work is complete shut the motor down following the manufacturer's instructions.
- 4- Ensure you clean all equipment after use. Excessive concrete build up can affect the performance of the machine.